

## Polishers

### L 602 VR

Order no. 329.800



Technical attributes	L 602 VR
Max. polishing pad diameter	220 mm
Max. back-up pad diameter	160 mm
Speed without load	400-800/2400 rpm
Power input	1500 watt
Power output	1000 watt
Tool fixture	M 14
Weight	3,30 kg

#### Variable-speed polisher with two grip variations

- Highly efficient and resilient motor for more power output
- VR electronic control: tachogenerator constant speed control, soft start with continuous speed control trigger, overload protection, temperature monitoring and speed selection with optimized low-speed range
- Integrated air deflection: protects against direct air flow
- Optimum handling by balanced weight distribution and 2 grip variants, depending on use
- Perfect cooling for heavy-duty use.
- Rubber rest bar protects machine and surface of workpiece when changing pads
- Powerful machine in compact, lightweight design
- Spindle lock

Standard equipment	
1 grip cover	259.508
1 side handle	252.721
1 bail handle	287.709

#### Accessories

##### Velcro pad



Soft and pliable for uniform pressure distribution, universal applications for holding polishing accessories, with centring hole and centring tube Ø 22 mm, adapter M 14

**Dimensions QTY/PKG: Order no.**  
**in mm:**

**160 Ø 1 252.583**

**FLEX Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
D-71711 Steinheim/Murr  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Polishers

### Velcro sponge, blue (hard)

---



Sponge with high tensile strength and coarse foam structure for polishing surfaces. Particularly suitable for extremely weathered or dull painted surfaces in combination with Flex special sanding polish (342.467). With centring hole, inner diameter 22 mm.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

**160 Ø x 30 1 304.751**

### Velcro sponge, yellow (coarse, hard)

---



Cambered, for polishing edges, extremely weathered or dull paint finishes and for paint treatment. With perforations, inner diameter 22 mm.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

**220 Ø x 20 1 256.908**

## FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
D-71711 Steinheim/Murr  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Polishers

### Velcro sponge, white (soft)

---



Fine, soft and extremely highly tear-proof polishing sponge for treatment of paint or varnish in combination with FLEX Pro paint sealant (342.475). With centring hole, inside diameter 22 mm.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

**160 Ø x 30 1 304.786**



Cambered, for polishing edges and for treating lacquer and lacquer varnish in combination with the Flex Profi lacquer varnish. With centring hole, inner diameter 22 mm.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

**220 Ø x 20 1 256.909**

### Velcro sponge, black (supersoft)

---



Extremely fine and soft for removing hologram effects and polish haze on dark paintwork in combination with FLEX special cutting polish (342.467). With centring hole, inside diameter 22 mm.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

**160 Ø x 30 1 304.824**

### Flexible backing pad

---



For M 14 backed lambswool.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

**175 Ø 1 123.862**

## FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
D-71711 Steinheim/Murr  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Polishers

### Backed fleece

---



Fiber backing with M 14 threaded flange, for removing scratches in glass and acrylics.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

125 Ø	1	122.726
-------	---	---------

175 Ø	1	122.734
-------	---	---------



Fiber backing with M 14 threaded flange, for removing scratches in glass and acrylics.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

125 Ø	1	122.726
-------	---	---------

175 Ø	1	122.734
-------	---	---------

### Spare fleece

---



With fiber backing.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

125 Ø	1	122.742
-------	---	---------

175 Ø	1	122.750
-------	---	---------

### Molleton buffing wheel

---



**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

125 Ø	1	123.749
-------	---	---------

**FLEX Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
D-71711 Steinheim/Murr  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Polishers

### Microfibre polishing cloth

---



Seamless, washable. For gentle removal of polishing and sealing residues. For a perfect surface finish and brilliant deep sheen.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

**400 x 400 1 317.098**

### Buffing wax

---

light/fine

**QTY/PKG: Order no.**

---

**1 123.811**

dark/medium

**QTY/PKG: Order no.**

---

**1 123.838**

red/coarse

**QTY/PKG: Order no.**

---

**1 123.846**

## FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
D-71711 Steinheim/Murr  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Polishers

### Abrasive compound

---



Innovative single-step cutting polish for the latest generation of scratch-proof paint. This polish can be used on new and old paint finishes without leaving hologram effects and polish haze, while achieving a deep shine with low dust production. Even on dark finishes, hologram effects and polish haze are easily removed. The right combination of polisher and lambswool/sponge is important for obtaining a perfect result.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

<b>250 ml</b>	<b>1</b>	<b>342.467</b>
<b>1000 ml</b>	<b>1</b>	<b>350.249</b>



Innovative single-step cutting polish for the latest generation of scratch-proof paint. This polish can be used on new and old paint finishes without leaving hologram effects and polish haze, while achieving a deep shine with low dust production. Even on dark finishes, hologram effects and polish haze are easily removed. The right combination of polisher and lambswool/sponge is important for obtaining a perfect result.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

<b>250 ml</b>	<b>1</b>	<b>342.467</b>
<b>1000 ml</b>	<b>1</b>	<b>350.249</b>

## FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
D-71711 Steinheim/Murr  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Polishers

### Profi high gloss polish

---



High-quality paint sealant formulation, based on organic and synthetic waxes, free of volatile silicones. Extremely high degree of sheen and paint protection. In one pass the nano-grinding particles permanently seal the paint finish, removing light hologram effects. The white sponges are best suited for use with this sealant.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

250 ml	1	342.475
1000 ml	1	350.257

### Velcro pad, cushioned

---



12 mm cellular rubber backing pads ensure uniform pressure distribution when polishing and sealing.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

125 Ø	1	350.737
150 Ø	1	350.745