

Floor and wall finishing

MS 1706 FR-Set

Order no. 329.673



Technical attributes	MS 1706 FR-Set
Cutting depth	0-35 mm
Groove width	10-30 mm
Disc Ø	140 mm
Speed without load	7500 rpm
Power input	1400 watt
Power output	950 watt
Tool fixture	M 14
Weight	3,70 kg

Wall chaser for push and pull cutting

- FR electronic control: with tachogenerator constant speed control, soft start, overload protection and temperature monitoring
- Patented swivel-mounted motor (EP1693169) allows for push and pull cutting.
- Optimal dust extraction and maximum safety due to enclosed guard
- Toolless blade changing and slit width adjustment
- Rotating adaptor for dust extractor
- Tool-free cutting depth adjustment
- Plunge cut stop
- Chases two parallel slots up to 35 mm deep and 30 mm wide
- Slot breaker for easy removal of the remaining material without a hammer

Standard equipment	
Diamantjet VI-Speedcut-cutting disc 140 mm Ø	334.464 (2x)
1 side handle	194.034
1 SDS-Clic quick-clamp nut M 14	253.049
Distance spacers	318.914 (5x)
Clamping flanges	191.612 (2x)
1 web remover	229.253
1 adapter for dust extractor	327.026
Cable clip	252.188 (3x)
1 plastic carry case	327.034

Accessories

Diamantjet VI - Speedcut



For cuts in walls, limestone, concrete and gas concrete. Thanks to the innovative HDS (high density sintered) technology, which can be recognised by the high density and homogeneity of the binding components, the Speedcut cutting disc stands out due to its uniform willingness to cut, its long life span and the overheating protection it offers. Due to the ribbed cover, only minimal pressure needs to be applied and the swarf is removed quickly: the workpiece is sliced through cleanly and smoothly.

Dimensions	QTY/PKG:	Order no.
in mm:		
140 Ø	1	334.464


FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Floor and wall finishing

Sharpening stone for diamond tools



Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

320 x 160 x 30	1	251.756
-------------------	---	---------